## NSN 5935-01-409-0707

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-409-0707

**Body Style:** Straight shape threaded **Overall Length:** 0.828 inches **Overall Diameter:** Between 1.202 inches and 1.234 inches **Distance From Mounting Shoulder To Front Face:** Between 0.411 inches and 0.442 inches **Mounting Facility Thickness:** 0.035 inches **Mating End Quantity: Contact Position Arrangement Style:** 14-12 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Nickel single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and copper single mating end single contact grouping and nickel single mating end single contact grouping **Insert Material:** Porcelain single mating end **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Stainless steel **Shell Surface Treatment:** 

Passivate and tin

Included Contact Quantity:

12 single mating end single contact grouping

**Bushing Accommodation Hole Shape:** 

Round

## NSN 5935-01-409-0707

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type:
Round pin single mating end single contact grouping
Special Features:
Solder flange mounted
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.500 gold grains, troy
Precious Material:
Gold
Supplementary Features:
Mounting method - flange
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A039b0