Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-411-0313

Thread	Class:

2b

**Thread Direction:** 

Right-hand

## **Body Style:**

Straight shape

# **Overall Length:**

1.740 inches

### **Overall Height:**

0.695 inches

## Overall Width:

0.298 inches

## **Unthreaded Mounting Hole Diameter:**

0.096 inches

# Distance Between Mounting Facility Centers:

1.500 inches

## Mating End Quantity:

1

## **Contact Position Arrangement Style:**

25 single mating end

# **Contact Removability:**

Nonremovable single mating end single contact grouping

# **Contact Maximum Current Rating In Amps:**

3.0 single mating end single contact grouping

### **Connector Locking Method:**

Friction

## Thread Size:

0.086 inches

# **Terminal Location:**

Back single mating end single contact grouping

### **Contact Material:**

Copper alloy single mating end single contact grouping

### **Contact Surface Treatment:**

Gold single mating end single contact grouping

### **Insert Material:**

Plastic polyethylene single mating end

# **Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end single contact grouping

### **Terminal Type:**

Printed circuit single mating end single contact grouping

### Unable To Decode:

Unable to decode and unable to decode

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity:

25 single mating end single contact grouping

#### **Special Features:**

Jackscrew type-female and location-right handandjackscrew type-female and location-left hand

**Precious Material:** 

Gold

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A039b0

## Mil-std (military Standard):

Mil-g-45204 spec.