NSN 5935-01-411-1958

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-411-1958

Body Style:
Straight shape, external coupling
Overall Length:
0.895 inches
Overall Height:
1.578 inches
Overall Width:
1.578 inches
Unthreaded Mounting Hole Diameter:
0.120 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.250 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.250 inches
Distance From Mounting Shoulder To Front Face:
Between 0.640 inches and 0.660 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
22-12 single mating end
Contact Removability:
Nonremovable single mating end all contact groupings
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Terminal Location:
Back single mating end all contact groupings
Contact Material:
Metal ferrous single mating end all contact groupings
Contact Surface Treatment:
Gold single mating end all contact groupings
Insert Material:
Glass single mating end
Terminal Type:
Solder well single mating end all contact groupings
Shell Material:

Metal ferrous

NSN 5935-01-411-1958

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Tin and nickel
Included Contact Quantity:
8 single mating end 2nd contact grouping
Included Contact Type:
Round pin single mating end all contact groupings
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.028 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-c-26482 spec.