## NSN 5935-01-411-4290

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-411-4290

Body Style:
Straight shape
Overall Length:
1.541 inches
Overall Height:
0.656 inches
Overall Width:
0.494 inches
Unthreaded Mounting Hole Diameter:
0.120 inches
Distance Between Mounting Facility Centers:
1.312 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
7 single mating end
Contact Removability:
Removable single mating end 1st contact grouping
Polarization Method:
Mating end
Shall Type:
Shell Type:
Solid
Solid
Solid  Connector Locking Method:
Solid  Connector Locking Method:  Friction
Solid  Connector Locking Method:  Friction  Terminal Location:
Solid  Connector Locking Method: Friction  Terminal Location: Back single mating end 1st contact grouping  Contact Material:
Solid  Connector Locking Method: Friction  Terminal Location: Back single mating end 1st contact grouping
Connector Locking Method: Friction Terminal Location: Back single mating end 1st contact grouping Contact Material: Copper alloy single mating end 1st contact grouping Contact Surface Treatment:
Solid  Connector Locking Method: Friction  Terminal Location: Back single mating end 1st contact grouping  Contact Material: Copper alloy single mating end 1st contact grouping
Connector Locking Method: Friction Terminal Location: Back single mating end 1st contact grouping Contact Material: Copper alloy single mating end 1st contact grouping Contact Surface Treatment: Gold single mating end 1st contact grouping Insert Material:
Connector Locking Method: Friction Terminal Location: Back single mating end 1st contact grouping Contact Material: Copper alloy single mating end 1st contact grouping Contact Surface Treatment: Gold single mating end 1st contact grouping Insert Material: Plastic diallyl phthalate single mating end
Connector Locking Method: Friction Terminal Location: Back single mating end 1st contact grouping Contact Material: Copper alloy single mating end 1st contact grouping Contact Surface Treatment: Gold single mating end 1st contact grouping Insert Material: Plastic diallyl phthalate single mating end Terminal Type:
Connector Locking Method: Friction  Terminal Location: Back single mating end 1st contact grouping  Contact Material: Copper alloy single mating end 1st contact grouping  Contact Surface Treatment: Gold single mating end 1st contact grouping  Insert Material: Plastic diallyl phthalate single mating end  Terminal Type: Solder well single mating end 1st contact grouping
Connector Locking Method: Friction Terminal Location: Back single mating end 1st contact grouping Contact Material: Copper alloy single mating end 1st contact grouping Contact Surface Treatment: Gold single mating end 1st contact grouping Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Solder well single mating end 1st contact grouping Shell Material:
Connector Locking Method: Friction Terminal Location: Back single mating end 1st contact grouping Contact Material: Copper alloy single mating end 1st contact grouping Contact Surface Treatment: Gold single mating end 1st contact grouping Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Solder well single mating end 1st contact grouping Shell Material: Steel
Connector Locking Method: Friction Terminal Location: Back single mating end 1st contact grouping Contact Material: Copper alloy single mating end 1st contact grouping Contact Surface Treatment: Gold single mating end 1st contact grouping Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Solder well single mating end 1st contact grouping Shell Material: Steel Shell Surface Treatment:
Connector Locking Method: Friction Terminal Location: Back single mating end 1st contact grouping Contact Material: Copper alloy single mating end 1st contact grouping Contact Surface Treatment: Gold single mating end 1st contact grouping Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Solder well single mating end 1st contact grouping Shell Material: Steel Shell Surface Treatment: Cadmium and chromate
Connector Locking Method: Friction Terminal Location: Back single mating end 1st contact grouping Contact Material: Copper alloy single mating end 1st contact grouping Contact Surface Treatment: Gold single mating end 1st contact grouping Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Solder well single mating end 1st contact grouping Shell Material: Steel Shell Surface Treatment:

Included Contact Type:

Round pin single mating end 1st contact grouping

## NSN 5935-01-411-4290

Electrical Receptacle Connector - Page 2 of 2



<b>Precious Material And Location:</b>
Contact surfaces gold
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A039b0