## NSN 5935-01-412-4938

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-412-4938 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling w/backshell **Overall Length:** 1.145 inches **Overall Height:** 1.500 inches **Overall Width:** 1.500 inches **Unthreaded Mounting Hole Diameter:** 0.120 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.156 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.156 inches **Cable Entrance Diameter:** Between 0.250 inches and 0.437 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 20-4 single mating end **Contact Removability:** Removable single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Externally threaded shell **Connector Cable Strain Relief Method:** Cable clamp **Thread Size:** 1.250 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

## NSN 5935-01-412-4938

Electrical Receptacle Connector - Page 2 of 2



Insert Material:
Rubber silicone class q single mating end
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum
Shell Surface Treatment:
Cadmium and chromate and nickel
Included Contact Quantity:
4 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material:
Gold
Test Data Document:
96906-ms3400dj20f4s standard (includes industry or association standards, individual manufactureer standards, etc.)
Thread Series Designator:
Unef
Specification Data:
81349-mil-c-5015 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-c-5015 spec.