## NSN 5935-01-412-5576

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-412-5576

**Body Style:** 

Angle shape w/cable clamp

**Overall Diameter:** 

1.969 inches

**Body Angle In Deg:** 

90.0

**Cable Entrance Diameter:** 

0.938 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

28a16 single mating end

**Contact Removability:** 

Removable single mating end all contact groupings

**Contact Maximum Current Rating In Amps:** 

235.0 single mating end 1st contact grouping

**Polarization Method:** 

Keyway or multiple keyway

**Insert Position In Deg:** 

0.0

Solid

Shell Type:

\_

**Connector Locking Method:** 

Bayonet slot

**Connector Cable Strain Relief Method:** 

Cable clamp

**Distance From Centerline To Connector End:** 

2.531 inches

**Distance From Centerline To Cable End:** 

1.968 inches

**Terminal Location:** 

Back single mating end all contact groupings

**Contact Material:** 

Copper alloy single mating end all contact groupings

**Contact Surface Treatment:** 

Silver single mating end all contact groupings

**Insert Material:** 

Rubber chloroprene class cr single mating end

**Terminal Type:** 

Crimp single mating end all contact groupings

**Shell Material:** 

Aluminum alloy

## NSN 5935-01-412-5576

Electrical Plug Connector - Page 2 of 2



Shell Surface Treatment:
Cadmium and chromate
Included Contact Quantity:
5 single mating end 2nd contact grouping
Included Contact Type:
Round socket single mating end all contact groupings
Precious Material And Location:
Contact surfaces silver
Precious Material And Weight:
0.025 silver grains, troy
Precious Material:
Silver
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A039b0