NSN 5935-01-412-9212

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-412-9212 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 29.7 millimeters **Overall Height:** 31.0 millimeters **Overall Width:** 31.0 millimeters **Environmental Protection:** Moisture proof and salt water resistant and vibration proof Center To Center Distance Between Mounting Facilities Parallel To Height: 24.6 millimeters Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 24.6 millimeters **Distance From Mounting Shoulder To Front Face:** 21.4 millimeters **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 15-18 single mating end **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Externally threaded shell **Thread Size:** 1.000 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Nickel single mating end single contact grouping and iron alloy 52 single mating end single contact grouping **Contact Surface Treatment:**

Terminal Type:

Solder well single mating end single contact grouping

Gold single mating end single contact grouping

NSN 5935-01-412-9212 Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Stainless steel
Shell Surface Treatment:
Passivate
Included Contact Quantity:
18 single mating end 2nd contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material:
Gold
Thread Series Designator:
Special acme
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0