NSN 5935-01-413-0370

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-413-0370 **Thread Class:** 2a and 2b **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape, internal coupling **Overall Length:** 1.370 inches **Overall Diameter:** 0.906 inches **Environmental Protection:** Humidity resistant and salt water resistant and shock proof and vibration proof **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 6-oct single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 and 105.0 and 140.0 and 215.0 and 265.0 Shell Type: Solid **Connector Locking Method:** Internally threaded shell

Thread Length:

0.190 inches and 0.260 inches

Thread Size:

0.625 inches and 0.688 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Glass single mating end

Terminal Type:

Crimp single mating end single contact grouping

NSN 5935-01-413-0370Electrical Plug Connector - Page 2 of 2



Shell Material:
Aluminum alloy
Shell Surface Treatment:
Nickel
Included Contact Quantity:
6 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.006 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-83723 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unef and unef
Specification Data:
81349-mil-c-83723/86 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0