Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-413-8633

#### **Body Style:**

Right angle type

## **Overall Length:**

4.550 inches

# **Overall Height:**

0.340 inches

## **Overall Width:**

0.286 inches

#### **Environmental Protection:**

Corrosion resistant and shock resistant and vibration resistant and moisture resistant

## **Unthreaded Mounting Hole Diameter:**

0.064 inches

## **Distance Between Mounting Facility Centers:**

4.350 inches

## Mating End Quantity:

1

## **Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

# **Contact Maximum Current Rating In Amps:**

3.0 single mating end single contact grouping

# **Polarization Method:**

Guide pin/socket

## Shell Type:

Solid

## **Connector Locking Method:**

Friction

## **Terminal Location:**

Side single mating end single contact grouping

## **Contact Material:**

Copper alloy single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

# **Terminal Type:**

Pin single mating end single contact grouping

# Shell Material:

Aluminum alloy 6061

# Shell Surface Treatment:

Anodize

# Included Contact Quantity:

79 single mating end single contact grouping

# Included Contact Type:

Round pin single mating end single contact grouping



Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.079 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0