

View Online at <https://aerobasegroup.com/nsn/5935-01-414-1143>

Body Style:

Straight shape

Overall Length:

19.0 millimeters

Overall Width:

8.0 millimeters

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

1.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

28.0 single mating end single contact grouping

Polarization Method:

Mating end

Connector Locking Method:

Friction

End Application:

Wasp class lhd, tarawa class lha, ticonderoga class cg (47), nimitz class cvn, sea wolf class ssn, arleigh burke class ddg, oliver perry class ffg, forrestal class cv, spruance class dd (963)

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Tin single mating end single contact grouping

Insert Material:

Plastic single mating end

Criticality Code Justification:

Feat

Terminal Type:

Pin single mating end single contact grouping

Included Contact Quantity:

10 single mating end single contact grouping

Included Contact Type:

Square pin single mating end single contact grouping

Special Features:

Weapon system essential

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0