NSN 5935-01-414-1143

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-414-1143

View Online at https://aerobasegroup.com/nsn/5935-01-414-1143
Body Style:
Straight shape
Overall Length:
19.0 millimeters
Overall Width:
8.0 millimeters
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
1.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
28.0 single mating end single contact grouping
Polarization Method:
Mating end
Connector Locking Method:
Friction
End Application:
Wasp class lhd, tarawa class lha, ticonderoga class cg (47), nimitz class cvn, sea wolf class ssn, arleigh burke class ddg, oliver perry
class ffg, forrestal class cv, spruance class dd (963)
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Tin single mating end single contact grouping
Insert Material:
Plastic single mating end
Criticality Code Justification:
Feat
Terminal Type:
Pin single mating end single contact grouping
Included Contact Quantity:
10 single mating end single contact grouping
Included Contact Type:
Square pin single mating end single contact grouping
Special Features:

N/a

Shelf Life:

Weapon system essential

NSN 5935-01-414-1143

Electrical Receptacle Connector - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A039b0