Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-414-8634

| B | ody Style: |
|----|--|
| St | traight shape |
| 0 | verall Length: |
| 1. | 590 inches |
| 0 | verall Height: |
| B | etween 5.150 inches and 5.170 inches |
| 0 | verall Width: |
| B | etween 5.156 inches and 5.176 inches |
| U | nthreaded Mounting Hole Diameter: |
| B | etween 0.146 inches and 0.156 inches |
| C | enter To Center Distance Between Mounting Facilities Parallel To Height: |
| 4. | 656 inches |
| D | istance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| 4. | 870 inches |
| D | istance From Mounting Shoulder To Front Face: |
| B | etween 1.098 inches and 1.108 inches |
| Μ | ating End Quantity: |
| 6 | |
| C | ontact Removability: |
| R | emovable all mating ends all contact groupings |
| P | olarization Method: |
| 3 | polarization posts |
| S | hell Type: |
| S | blid |
| C | onnector Locking Method: |
| Fr | iction |
| Te | erminal Location: |
| Ba | ack all mating ends all contact groupings |
| Te | erminal Type: |
| С | rimp all mating ends all contact groupings |
| S | hell Material: |
| M | etal |
| In | cluded Contact Quantity: |
| 33 | 32 all mating ends all contact groupings |
| S | pecial Features: |
| Eı | mi/rfi spring fingers |
| S | helf Life: |
| N | /a |
| U | nit Of Measure: |
| | |
| D | emilitarization: |
| N | 0 |

NSN 5935-01-414-8634

Electrical Receptacle Connector - Page 2 of 2

Fiig: A039b0

