

View Online at <https://aerobasegroup.com/nsn/5935-01-414-9147>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape w/flange

Overall Length:

1.310 inches

Overall Height:

1.000 inches

Overall Width:

1.000 inches

Unthreaded Mounting Hole Diameter:

0.125 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.718 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.718 inches

Distance From Mounting Shoulder To Front Face:

0.580 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

2

Contact Position Arrangement Style:

Sma 2nd mating end

Contact Removability:

Nonremovable all mating ends single contact grouping

Shell Type:

Solid

Connector Locking Method:

Bayonet pin and externally threaded shell

End Application:

An-alr56c

Thready Qty Per Inch (tpi):

36

Thread Size:

0.250 inches

Contact Material:

Copper alloy all mating ends single contact grouping

Contact Surface Treatment:

Gold all mating ends single contact grouping

Insert Material:

Plastic polytetrafluoroethylene all mating ends

Contact Surface Treatment Specification:

Mil-g-45204, type ii, class 2 military specification single treatment response all mating ends single contact grouping

Contact Material Specification:

Qq-c-530, condition h federal specification single material response all mating ends single contact grouping

Shell Material:

Steel comp 303

Shell Surface Treatment:

Nickel and passivate

Shell Surface Treatment Specification:

Mil-c-26074 military specification 1st treatment response and qq-p-35 federal specification 2nd treatment response

Shell Material Specification:

Qq-s-763, condition a federal specification single material response

Insert Material Specification:

Mil-p-19468 military specification single material response all mating ends

Included Contact Quantity:

1 all mating ends single contact grouping

Included Contact Type:

Round socket all mating ends single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.010 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.