Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-414-9980

# Body Style:

Straight shape, external coupling

**Overall Length:** 

1.243 inches

# **Overall Diameter:**

1.386 inches

### **Distance From Mounting Shoulder To Front Face:**

0.915 inches

#### Mounting Facility Thickness:

Between 0.062 inches and 0.125 inches

# Mating End Quantity:

1

### **Contact Position Arrangement Style:**

4-nov single mating end

### **Connector Locking Method:**

Bayonet pin

### **Terminal Location:**

Back single mating end single contact grouping

### **Contact Material:**

Copper alloy single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping

# **Terminal Type:**

Solder well single mating end single contact grouping

# Included Contact Quantity:

4 single mating end single contact grouping

# **Bushing Accommodation Hole Shape:**

Round w/flat

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material And Weight:** 

0.004 gold grains, troy

## **Precious Material:**

Gold

# Test Data Document:

81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

96906-ms27468 government standard

# Shelf Life:

N/a

Unit Of Measure:

Electrical Receptacle Connector - Page 2 of 2



Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-38999 spec.