NSN 5935-01-415-6858



Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-01-415-6858 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape spring mount **Overall Length:** 1.512 inches **Overall Diameter:** 1.855 inches **Environmental Protection:** Thermal shock resistant and pressure proof and vibration resistant and heat resistant and cold resistant **Threaded Device Type:** Back shell **Mating End Quantity: Contact Position Arrangement Style:** 27-2 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 20.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Friction **Thread Size:** 1.062 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Glass single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 1, gr a military specification single treatment response single mating end single contact grouping

NSN 5935-01-415-6858

Electrical Receptacle Connector - Page 2 of 2



| Terminal Type: |
|--|
| Crimp single mating end single contact grouping |
| Shell Material: |
| Aluminum alloy |
| Shell Surface Treatment: |
| Chromate and cadmium |
| Shell Surface Treatment Specification: |
| Qq-p-416, type 2, cl 3 federal specification all treatment responses |
| Included Contact Quantity: |
| 14 single mating end single contact grouping |
| Bushing Accommodation Hole Shape: |
| Round keyed |
| Included Contact Type: |
| Round socket single mating end single contact grouping |
| Precious Material And Location: |
| Contact surfaces gold |
| Precious Material And Weight: |
| 0.014 gold grains, troy |
| Precious Material: |
| Gold |
| Supplementary Features: |
| Mounting method - spring clip |
| Thread Series Designator: |
| Unef |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |
| Mil-std (military Standard): |
| Mil-g-45204 spec. |
| |