

View Online at <https://aerobasegroup.com/nsn/5935-01-415-6860>

Body Style:

Straight shape, internal coupling

Overall Length:

Between 0.225 inches and 0.238 inches

Environmental Protection:

Heat resistant and cold resistant and thermal shock resistant and pressure proof and fungus resistant and corrosion resistant and vibration resistant

Cable Entrance Diameter:

Between 0.249 inches and 0.275 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

Bnc single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

900.0 single mating end single contact grouping

Contact Maximum Frequency Rating:

2.0 megahertz single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Bayonet slot

Connector Cable Strain Relief Method:

Crimp type

End Application:

Aircraft, prowler ea-6b; aircraft, tomcat f-14

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping and copper alloy single mating end single contact grouping

Insert Material:

Plastic polytetrafluoroethylene single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, gr c, cl 1 military specification single treatment response single mating end single contact grouping and qq-n-290 federal specification 2nd treatment response single mating end single contact grouping

Criticality Code Justification:

Feat

Terminal Type:

Crimp single mating end single contact grouping

Contact Material Specification:

Astm b16 assn standard single material response single mating end single contact grouping

Shell Material:

Tin

Shell Surface Treatment:

Nickel

Shell Material Specification:

Mil-t-10727 military specification single material response

Insert Material Specification:

Astm-d1457-83 assn standard single material response single mating end

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial socket single mating end single contact grouping

Special Features:

Weapon system essential

Precious Material And Location:

Contact surface gold

Precious Material And Weight:

0.005 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.