# NSN 5935-01-417-8412

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-417-8412

**Body Style:** 

Straight shape, external coupling

Overall Length:

1.243 inches

**Overall Diameter:** 

1.625 inches

#### **Environmental Protection:**

Moisture proof and salt water resistant and vibration proof and corrosion resistant and dust resistant and fuel resistant and fungus resistant and humidity resistant and oil resistant and shock resistant and thermal shock resistant and vibration resistant

# **Distance From Mounting Shoulder To Front Face:**

0.915 inches

#### **Mounting Facility Thickness:**

Between 0.062 inches and 0.125 inches

#### **Mating End Quantity:**

.

# **Contact Position Arrangement Style:**

15-15 single mating end

#### **Terminal Location:**

Back single mating end all contact groupings

# **Contact Material:**

Copper alloy single mating end all contact groupings

# **Contact Surface Treatment:**

Gold single mating end all contact groupings

# **Terminal Type:**

Crimp single mating end all contact groupings

# **Shell Surface Treatment:**

Cadmium

# **Included Contact Quantity:**

14 single mating end 2nd contact grouping

# **Included Contact Type:**

Round socket single mating end all contact groupings

# **Precious Material And Location:**

Contact surfaces gold

# **Precious Material:**

Gold

#### **Test Data Document:**

81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# **Specification Data:**

96906-ms27467 government standard

# Shelf Life:

N/a

# **Unit Of Measure:**

# NSN 5935-01-417-8412

Electrical Receptacle Connector - Page 2 of 2



Demi			

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-38999 spec.