Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-417-9266

| Thread Class: |
|---|
| 2b and 2a |
| Thread Direction: |
| Right-hand |
| Body Style: |
| Right angle type |
| Overall Length: |
| Between 1.526 inches and 1.556 inches |
| Overall Width: |
| 0.881 inches |
| Body Height: |
| Between 0.479 inches and 0.509 inches |
| Distance Between Mounting Facility Centers: |
| 1.312 inches |
| Threaded Device Type: |
| Mounting stud |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| "2, 15" single mating end |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Friction and jackscrew-socket |
| Thread Size: |
| 0.112 inches |
| Terminal Location: |
| Side single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping |
| Terminal Type: |
| Printed circuit single mating end single contact grouping |
| Shell Material: |
| Aluminum alloy |
| Included Contact Quantity: |
| 15 single mating end single contact grouping |
| Included Contact Type: |
| Round socket single mating end single contact grouping |
| |



Precious Material And Location: Contact surfaces gold Precious Material And Weight: 0.015 gold grains, troy Precious Material: Gold Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: --

No

Fiig:

A039b0