NSN 5935-01-418-1744

Electrical Plug Connector - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5935-01-418-1744

Body Style: Straight shape w/strain relief Mating End Quantity: 1 Contact Removability: Removable single mating end single contact grouping Contact Maximum Current Rating In Amps: 400.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 600.0 single mating end single contact grouping Shell Type: Solid Connector Locking Method: Friction Connector Cable Strain Relief Method: Cord grip Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Contact Surface Treatment Specification: Qq-s-365 federal specification single treatment response single mating end single contact grouping Terminal Type: Crimp single mating end single contact grouping Included Contact Type: Round socket single mating end single contact grouping
Mating End Quantity: 1 Contact Removability: Removable single mating end single contact grouping Contact Maximum Current Rating In Amps: 400.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 600.0 single mating end single contact grouping Shell Type: Solid Connector Locking Method: Friction Connector Cable Strain Relief Method: Cord grip Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Contact Surface Treatment Specification: Qq-s-365 federal specification single treatment response single mating end single contact grouping Terminal Type: Crimp single mating end single contact grouping Included Contact Type:
Contact Removability: Removable single mating end single contact grouping Contact Maximum Current Rating In Amps: 400.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 600.0 single mating end single contact grouping Shell Type: Solid Connector Locking Method: Friction Connector Cable Strain Relief Method: Cord grip Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Contact Surface Treatment Specification: Qq-s-365 federal specification single treatment response single mating end single contact grouping Terminal Type: Crimp single mating end single contact grouping Included Contact Type:
Contact Removability: Removable single mating end single contact grouping Contact Maximum Current Rating In Amps: 400.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 600.0 single mating end single contact grouping Shell Type: Solid Connector Locking Method: Friction Connector Cable Strain Relief Method: Cord grip Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Contact Surface Treatment Specification: Qq-s-365 federal specification single treatment response single mating end single contact grouping Terminal Type: Crimp single mating end single contact grouping Included Contact Type:
Contact Maximum Current Rating In Amps: 400.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 600.0 single mating end single contact grouping Shell Type: Solid Connector Locking Method: Friction Connector Cable Strain Relief Method: Cord grip Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Silver single mating end single treatment response single mating end single contact grouping Terminal Type: Crimp single mating end single contact grouping Terminal Type:
Contact Maximum Current Rating In Amps: 400.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 600.0 single mating end single contact grouping Shell Type: Solid Connector Locking Method: Friction Connector Cable Strain Relief Method: Cord grip Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Contact Surface Treatment Specification: Qq-s-365 federal specification single treatment response single mating end single contact grouping Terminal Type: Crimp single mating end single contact grouping Included Contact Type:
Contact Maximum Ac Voltage Rating In Volts: 600.0 single mating end single contact grouping Shell Type: Solid Connector Locking Method: Friction Connector Cable Strain Relief Method: Cord grip Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Contact Surface Treatment Specification: Qq-s-365 federal specification single treatment response single mating end single contact grouping Terminal Type: Crimp single mating end single contact grouping Included Contact Type:
Contact Maximum Ac Voltage Rating In Volts: 600.0 single mating end single contact grouping Shell Type: Solid Connector Locking Method: Friction Connector Cable Strain Relief Method: Cord grip Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Contact Surface Treatment Specification: Qq-s-365 federal specification single treatment response single mating end single contact grouping Terminal Type: Crimp single mating end single contact grouping Included Contact Type:
Shell Type: Solid Connector Locking Method: Friction Connector Cable Strain Relief Method: Cord grip Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Contact Surface Treatment Specification: Qq-s-365 federal specification single treatment response single mating end single contact grouping Terminal Type: Crimp single mating end single contact grouping Included Contact Type:
Shell Type: Solid Connector Locking Method: Friction Connector Cable Strain Relief Method: Cord grip Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Contact Surface Treatment Specification: Qq-s-365 federal specification single treatment response single mating end single contact grouping Terminal Type: Crimp single mating end single contact grouping Included Contact Type:
Connector Locking Method: Friction Connector Cable Strain Relief Method: Cord grip Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Contact Surface Treatment Specification: Qq-s-365 federal specification single treatment response single mating end single contact grouping Terminal Type: Crimp single mating end single contact grouping Included Contact Type:
Connector Locking Method: Friction Connector Cable Strain Relief Method: Cord grip Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Contact Surface Treatment Specification: Qq-s-365 federal specification single treatment response single mating end single contact grouping Terminal Type: Crimp single mating end single contact grouping Included Contact Type:
Connector Cable Strain Relief Method: Cord grip Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Contact Surface Treatment Specification: Qq-s-365 federal specification single treatment response single mating end single contact grouping Terminal Type: Crimp single mating end single contact grouping Included Contact Type:
Connector Cable Strain Relief Method: Cord grip Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Contact Surface Treatment Specification: Qq-s-365 federal specification single treatment response single mating end single contact grouping Terminal Type: Crimp single mating end single contact grouping Included Contact Type:
Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Contact Surface Treatment Specification: Qq-s-365 federal specification single treatment response single mating end single contact grouping Terminal Type: Crimp single mating end single contact grouping Included Contact Type:
Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Contact Surface Treatment Specification: Qq-s-365 federal specification single treatment response single mating end single contact grouping Terminal Type: Crimp single mating end single contact grouping Included Contact Type:
Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Contact Surface Treatment Specification: Qq-s-365 federal specification single treatment response single mating end single contact grouping Terminal Type: Crimp single mating end single contact grouping Included Contact Type:
Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Contact Surface Treatment Specification: Qq-s-365 federal specification single treatment response single mating end single contact grouping Terminal Type: Crimp single mating end single contact grouping Included Contact Type:
Contact Surface Treatment: Silver single mating end single contact grouping Contact Surface Treatment Specification: Qq-s-365 federal specification single treatment response single mating end single contact grouping Terminal Type: Crimp single mating end single contact grouping Included Contact Type:
Contact Surface Treatment: Silver single mating end single contact grouping Contact Surface Treatment Specification: Qq-s-365 federal specification single treatment response single mating end single contact grouping Terminal Type: Crimp single mating end single contact grouping Included Contact Type:
Silver single mating end single contact grouping Contact Surface Treatment Specification: Qq-s-365 federal specification single treatment response single mating end single contact grouping Terminal Type: Crimp single mating end single contact grouping Included Contact Type:
Contact Surface Treatment Specification: Qq-s-365 federal specification single treatment response single mating end single contact grouping Terminal Type: Crimp single mating end single contact grouping Included Contact Type:
Qq-s-365 federal specification single treatment response single mating end single contact grouping Terminal Type: Crimp single mating end single contact grouping Included Contact Type:
Terminal Type: Crimp single mating end single contact grouping Included Contact Type:
Crimp single mating end single contact grouping Included Contact Type:
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces silver
Precious Material And Weight:
0.005 silver grains, troy
Precious Material:
Silver
Shelf Life:
N/a
N/a
Unit Of Measure:
Unit Of Measure:

A039b0