Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-418-5354

Body Style:
Straight shape
Overall Length:
0.880 inches
Overall Diameter:
0.320 inches
Distance From Mounting Shoulder To Front Face:
Between 0.414 inches and 0.440 inches
Mounting Facility Thickness:
Between 0.023 inches and 0.096 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
Smc single mating end
Contact Removability:
Removable single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Push-pull
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Included Contact Quantity:
1 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round w/flat
Included Contact Type:
Coaxial pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.005 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-39012 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification

format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Electrical Receptacle Connector - Page 2 of 2



Specification Data:

81349-mil-c-39012/76 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0