NSN 5935-01-420-4786

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-420-4786 **Thread Class:** 2a and 2b **Thread Direction:** Right-hand and right-hand **Body Style:** Straight type **Overall Length:** 2.350 inches **Overall Height:** 0.335 inches **Overall Width:** 0.250 inches **Unthreaded Mounting Hole Diameter:** 0.120 inches **Distance Between Mounting Facility Centers:** 2.100 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 2 rows of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Polarization Method:** Jackscrew **Connector Locking Method:** Jackscrew-socket **End Application:** Lgm030g Thready Qty Per Inch (tpi): 56 and 56 **Thread Size:** 0.086 inches and 0.086 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

NSN 5935-01-420-4786

No Fiig: A039b0

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Wire wrap single mating end single contact grouping
Unable To Decode:
Unable to decode and unable to decode
Included Contact Quantity:
30 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Special Features:
Jackscrew type-female and location-right handandjackscrew type-male and location-left hand
Thread Series Designator:
Unc and unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization: