## NSN 5935-01-420-4787

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-420-4787 **Thread Class:** 2a and 2b **Thread Direction:** Right-hand and right-hand **Body Style:** Straight type **Overall Length:** 1.850 inches **Overall Height:** 0.335 inches **Overall Width:** 0.250 inches **Unthreaded Mounting Hole Diameter:** 0.120 inches **Distance Between Mounting Facility Centers:** 1.600 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 2 rows of contacts non-inserted board single mating end **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Polarization Method:** Jackscrew Shell Type: Solid **Connector Locking Method:** Jackscrew-socket **End Application:** Lgm030g Thready Qty Per Inch (tpi): 56 and 56 **Thread Size:** 0.086 inches and 0.086 inches **Terminal Location:** Back single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end

**Terminal Type:** 

Wire wrap single mating end single contact grouping

## NSN 5935-01-420-4787

Electrical Receptacle Connector - Page 2 of 2



Unable To Decode:
Unable to decode and unable to decode
Included Contact Quantity:

20 single mating end single contact grouping

**Included Contact Type:** 

Round socket single mating end single contact grouping

**Special Features:** 

Jackscrew type-female and location-right handandjackscrew type-male and location-left hand

**Thread Series Designator:** 

Unc and unc

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A039b0