Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-420-4790

### Thread Class:

2a and 2b

# **Thread Direction:**

Right-hand and right-hand

## **Body Style:**

Straight type

### **Overall Length:**

1.350 inches

#### **Overall Height:**

0.335 inches

#### **Overall Width:**

0.250 inches

### **Unthreaded Mounting Hole Diameter:**

0.120 inches

### **Distance Between Mounting Facility Centers:**

1.100 inches

Threaded Device Type:

Coupling facility

## Mating End Quantity:

1

### **Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

### **Contact Removability:**

Nonremovable single mating end single contact grouping

### **Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

#### **Polarization Method:**

Jackscrew

### **Connector Locking Method:**

Jackscrew-socket

#### **End Application:**

Lgm030g

#### Thready Qty Per Inch (tpi):

56 and 56

#### **Thread Size:**

0.086 inches and 0.086 inches

## **Terminal Location:**

Back single mating end single contact grouping

## **Contact Material:**

Copper alloy single mating end single contact grouping

## **Insert Material:**

Plastic diallyl phthalate single mating end



### **Terminal Type:**

Wire wrap single mating end single contact grouping

### Unable To Decode:

Unable to decode and unable to decode

# Included Contact Quantity:

10 single mating end single contact grouping

# Included Contact Type:

Round socket single mating end single contact grouping

# **Special Features:**

Jackscrew type-female and location-right handandjackscrew type-male and location-left hand

### Thread Series Designator:

Unc and unc

Shelf Life:

N/a

#### Unit Of Measure:

---

# Demilitarization:

No

## Fiig:

A039b0