

View Online at <https://aerobasegroup.com/nsn/5935-01-420-6203>

Thread Class:

2a and 2b and 2a

Thread Direction:

Right-hand and right-hand and right-hand

Body Style:

Straight shape

Overall Length:

Between 2.840 inches and 2.860 inches

Overall Height:

Between 0.707 inches and 0.717 inches

Overall Width:

Between 0.245 inches and 0.255 inches

Distance Between Mounting Facility Centers:

Between 2.645 inches and 2.655 inches

Threaded Device Type:

Coupling facility and mounting stud

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Polarization Method:

Jackscrew

Connector Locking Method:

Jackscrew-socket

Thread Length:

0.130 inches

Thready Qty Per Inch (tpi):

56 and 56 and 56

Thread Size:

0.086 inches and 0.086 inches and 0.086 inches

Terminal Location:

Back single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Crimp and solder single mating end single contact grouping

Included Contact Quantity:

50 single mating end single contact grouping

Special Features:

Jackscrew type-male and location-right hand top

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.300 gold ounces, troy

Precious Material:

Gold

Thread Series Designator:

Un

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0