Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-422-2094

## **Body Style:**

Straight shape

#### **Overall Length:**

1.000 inches

## **Overall Height:**

Between 0.518 inches and 0.548 inches

#### **Overall Width:**

0.190 inches

#### Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

#### **Contact Removability:**

Nonremovable single mating end single contact grouping

## **Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

## Connector Locking Method:

Friction

## **Operating Tempurature Rating:**

Between -40.0 degrees celsius and 105.0 degrees celsius

## **Terminal Location:**

Back single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

## **Contact Surface Treatment:**

Gold single mating end single contact grouping

## **Insert Material:**

Plastic polyamide glass filled single mating end

## **Contact Surface Treatment Specification:**

Mil-g-45204, type ii, grade c, class 1 military specification single treatment response single mating end single contact grouping

#### **Terminal Type:**

Printed circuit single mating end single contact grouping

## **Contact Material Specification:**

Qq-b-750 federal specification single material response single mating end single contact grouping

#### **Included Contact Quantity:**

20 single mating end single contact grouping

## Included Contact Type:

Square pin single mating end single contact grouping

## **Precious Material And Location:**

Contact surfaces gold

#### **Precious Material And Weight:**

0.020 gold grains, troy

Electrical Receptacle Connector - Page 2 of 2



**Precious Material:** 

Gold

Shelf Life:

N/a

Unit Of Measure:

--

## Demilitarization:

No

Fiig:

A039b0

# Mil-std (military Standard):

Mil-g-45204 spec.