NSN 5935-01-422-8563

Thread Class:

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-422-8563

2b
Thread Direction:
Right-hand
Body Style:
Straight shape, internal coupling
Overall Length:
1.938 inches
Overall Diameter:
2.329 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
33-155 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Key, multiple key groove
Insert Position In Deg:
0.0 and 49.0 and 169.0 and 200.0 and 257.0
Shell Type:
Solid
Connector Locking Method:
Internally threaded shell
Thready Qty Per Inch (tpi):
10
Thread Size:
2.000 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic fluorosilicone single mating end
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy

NSN 5935-01-422-8563Electrical Plug Connector - Page 2 of 2



Shell Surface Treatment:
Cadmium and chromate and nickel
Included Contact Quantity:
155 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.155 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-28840 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Double stub
Specification Data:
81349-mil-c-28840/16 government specification
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A039b0