## NSN 5935-01-423-2260

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-423-2260 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.248 inches **Overall Height:** 0.812 inches **Overall Width:** 0.812 inches **Environmental Protection:** Humidity resistant and salt water resistant and shock proof and vibration proof **Unthreaded Mounting Hole Diameter:** Between 0.116 inches and 0.125 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.594 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.594 inches **Distance From Mounting Shoulder To Front Face:** 0.480 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 803 single mating end **Contact Removability:** Removable single mating end single contact grouping Shell Type: Solid **Operating Tempurature Rating:** Between -65.0 degrees celsius and 200.0 degrees celsius **Thread Size:** 0.562 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

## NSN 5935-01-423-2260

Electrical Receptacle Connector - Page 2 of 2



Insert Material:
Plastic epoxy single mating end
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Stainless steel
Shell Surface Treatment:
Passivate
Included Contact Quantity:
3 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material:
Gold
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0