

View Online at <https://aerobasegroup.com/nsn/5935-01-425-0655>

**Body Style:**

Rectangular shape

**Overall Length:**

2.282 inches

**Overall Height:**

0.691 inches

**Overall Width:**

Between 0.479 inches and 0.509 inches

**Environmental Protection:**

Heat resistant and cold resistant

**Unthreaded Mounting Hole Diameter:**

Between 0.152 inches and 0.160 inches

**Distance Between Mounting Facility Centers:**

2.500 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

37 single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

1.0 single mating end single contact grouping

**Polarization Method:**

Mating end

**Shell Type:**

Solid

**Connector Locking Method:**

Friction

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate glass filled single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping

**Terminal Type:**

Insulation piercing single mating end single contact grouping

**Shell Material:**

Steel

**Shell Surface Treatment:**

Tin

**Included Contact Quantity:**

37 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.037 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.