Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-425-0658

Body Style:
Rectangular shape
Overall Length:
1.213 inches
Overall Height:
0.693 inches
Overall Width:
Between 0.479 inches and 0.509 inches
Environmental Protection:
Cold resistant and heat resistant
Unthreaded Mounting Hole Diameter:
Between 0.152 inches and 0.160 inches
Distance Between Mounting Facility Centers:
0.984 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
9 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
1.0 single mating end single contact grouping
Polarization Method:
Mating end
Shell Type:
Solid
Connector Locking Method:
Friction
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate glass filled single mating end
Contact Surface Treatment Specification:
Mil-g-45204 military specification 1st treatment response single mating end single contact grouping
Terminal Type:
Insulation piercing single mating end single contact grouping
Shell Material:
Ota al

Steel

NSN 5935-01-425-0658

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:

Tin

Included Contact Quantity:

9 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.009 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.