NSN 5935-01-426-0094

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-426-0094 **Thread Class:** 2a and 2b **Thread Direction:** Right-hand **Body Style:** Straight shape, internal coupling **Overall Length:** 2.125 inches **Overall Diameter:** 1.594 inches **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 22-28 single mating end **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 280.0 Shell Type: Solid **Connector Locking Method:** Internally threaded coupling ring **Thread Size:** 1.312 inches and 1.375 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and nickel single mating end single contact grouping **Insert Material:** Rubber silicone class q single mating end **Terminal Type:** Crimp single mating end single contact grouping

Shell Material:

Stainless steel

Shell Surface Treatment:

Cadmium and chromate and nickel

Included Contact Quantity:

7 single mating end single contact grouping

NSN 5935-01-426-0094

Electrical Plug Connector - Page 2 of 2



Inc	luded	d Con	tact	Type:
	IUUC	4 O OH	ıavı	IVDC.

Round pin single mating end single contact grouping

Precious Material:

Gold

Test Data Document:

81349-mil-c-5015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef

Specification Data:

96906-ms3406 government standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-5015 spec.