NSN 5935-01-426-2049

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-426-2049

| Thread Class: |
|--|
| 2a and 2b |
| Thread Direction: |
| Right-hand and right-hand |
| Body Style: |
| Straight shape, internal coupling |
| Overall Length: |
| 1.938 inches |
| Overall Diameter: |
| 1.141 inches |
| Environmental Protection: |
| Moisture resistant and corrosion resistant and thermal shock resistant and vibration resistant and heat resistant and cold resistant |
| Threaded Device Type: |
| Back shell and coupling facility |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| Err-090 single mating end |
| Contact Removability: |
| Removable single mating end single contact grouping |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Internally threaded coupling ring |
| Thready Qty Per Inch (tpi): |
| 20 and 10 |
| Thread Size: |
| 0.875 inches and 0.875 inches |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping |
| Insert Material: |
| Plastic fluorosilicone single mating end |
| Terminal Type: |
| Crimp single mating end single contact grouping |
| Shell Material: |
| Aluminum |

Cadmium and chromate and nickel

Shell Surface Treatment:

NSN 5935-01-426-2049

Fiig: A039b0

Electrical Plug Connector - Page 2 of 2



| Included Contact Quantity: |
|--|
| 12 single mating end single contact grouping |
| Included Contact Type: |
| Round socket single mating end single contact grouping |
| Precious Material And Location: |
| Contact surfaces gold |
| Precious Material And Weight: |
| 0.012 gold grains, troy |
| Precious Material: |
| Gold |
| Test Data Document: |
| 81349-mil-c-28840 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Thread Series Designator: |
| Unef and double stub |
| Specification Data: |
| 81349-mil-c-28840/16 government specification |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |