NSN 5935-01-429-2307



Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-01-429-2307 **Thread Class:** 2a **Thread Direction:** Left-hand and left-hand **Body Style:** Straight shape, external coupling **Overall Length:** 31.5 millimeters **Overall Height:** 31.0 millimeters **Overall Width:** 31.0 millimeters Center To Center Distance Between Mounting Facilities Parallel To Height: 24.6 millimeters Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 24.6 millimeters **Distance From Mounting Shoulder To Front Face:** 19.5 millimeters **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 15-35 single mating end **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Externally threaded shell **End Application:** Pacer dawn Thready Qty Per Inch (tpi): 10 **Thread Size:** 22.0 millimeters and 1.000 inches **Terminal Location:** Front single mating end single contact grouping

Terminal Type: Crimp single mating end single contact grouping

Shell Surface Treatment:

Nickel

NSN 5935-01-429-2307

Electrical Receptacle Connector - Page 2 of 2



Thread Tolerance Class:
6g external
Included Contact Quantity:
37 single mating end single contact grouping
Supplementary Features:
Mounting method - flange
Thread Series Designator:
Iso m and special acme
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A039b0