NSN 5935-01-433-8843

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-433-8843

Body Style:

Straight shape, external coupling

Overall Length:

1.289 inches

Overall Height:

1.312 inches

Overall Width:

1.312 inches

Environmental Protection:

Dust resistant and fungus resistant and moisture proof and salt spray proof and humidity resistant and shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

0.128 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.531 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.531 inches

Distance From Mounting Shoulder To Front Face:

0.820 inches

Mating End Quantity:

Contact Position Arrangement Style:

17-99 single mating end

Contact Removability:

Removable single mating end all contact groupings

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Operating Tempurature Rating:

Between -65.0 degrees celsius and 175.0 degrees celsius

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end all contact groupings

Insert Material:

Plastic epoxy single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end all contact groupings

Terminal Type:

Crimp single mating end all contact groupings

NSN 5935-01-433-8843

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Aluminum alloy
Shell Surface Treatment:
Nickel
Shell Surface Treatment Specification:
Mil-c-26707, cl 3 or 4, grade b military specification single treatment response
Included Contact Quantity:
21 single mating end 2nd contact grouping
Included Contact Type:
Round pin single mating end all contact groupings
Precious Material And Location:
Contact surfaces gold
Precious Material:
Gold
Test Data Document:
81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
96906-ms27656 government standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.