## NSN 5935-01-434-8483

**Terminal Type:** 

**Shell Material:**Metal ferrous

Crimp single mating end single contact grouping

Electrical Plug Connector - Page 1 of 2



Licenseal rag connector rage relia
View Online at https://aerobasegroup.com/nsn/5935-01-434-8483
Thread Class:
2a and 2b
Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape, internal coupling w/backshell
Overall Length:
2.500 inches
Overall Diameter:
2.463 inches
Environmental Protection:
Moisture proof and salt water resistant
Threaded Device Type:
Back shell and coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
Fk-l32 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling ring
Thread Length:
0.467 inches
Thready Qty Per Inch (tpi):
18 and 18
Thread Size:
2.000 inches and 2.000 inches
Terminal Location:
Back single mating end single contact grouping
Insert Material:
Silicon single mating end

## **NSN 5935-01-434-8483**Electrical Plug Connector - Page 2 of 2



Shell Surface Treatment:
Cadmium
Included Contact Quantity:
4 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Thread Series Designator:
Uns and uns
Specification Data:
96906-ms3459kt32-s government standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):

Mil-dtl-5015 spec.