NSN 5935-01-436-8280

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-436-8280

Body Style:

Straight shape, external coupling

Overall Length:

1.289 inches

Overall Height:

1.031 inches

Overall Width:

1.031 inches

Environmental Protection:

Corrosion resistant and dust resistant and humidity resistant

Unthreaded Mounting Hole Diameter:

0.128 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.406 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.406 inches

Distance From Mounting Shoulder To Front Face:

0.820 inches

Mating End Quantity:

Contact Position Arrangement Style:

11-35 single mating end

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0 and 95.0 and 132.0 and 232.0 and 260.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Operating Tempurature Rating:

Between -65.0 degrees celsius and 175.0 degrees celsius

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic epoxy single mating end

NSN 5935-01-436-8280

Demilitarization:

Mil-g-45204 spec.

Mil-std (military Standard):

No Fiig: A039b0

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Passivate
Included Contact Quantity:
13 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material:
Gold
Test Data Document:
81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
96906-ms27656 government standard
Shelf Life:
N/a
Unit Of Measure:
