

View Online at <https://aerobasegroup.com/nsn/5935-01-441-3610>

Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Straight shape, flange mount

Overall Length:

0.739 inches

Bushing Diameter:

0.382 inches

Overall Height:

0.538 inches

Environmental Protection:

Moisture resistant and shock proof and vibration proof

Distance Between Mounting Facility Centers:

0.593 inches

Cable Entrance Diameter:

0.145 inches

Threaded Device Type:

Mounting hole

Mating End Quantity:

1

Contact Position Arrangement Style:

Nonstd single mating end

Shell Type:

Solid

Connector Locking Method:

Friction

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

End Application:

Pacer dawn

Thready Qty Per Inch (tpi):

56

Thread Size:

0.086 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204, type 2, cl 2 military specification single treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Steel

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial pin single mating end single contact grouping

Special Features:

Tolerances + or - .005; dwg name connector, coaxial, rf

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.005 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.