NSN 5935-01-444-3959

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-444-3959

Body Style:
Right angle type
Overall Length:
8.495 inches
Overall Height:
0.760 inches
Body Width:
0.390 inches
Body Height:
0.540 inches
Environmental Protection:
Shock resistant and vibration resistant and corrosion resistant and humidity resistant and fungus resistant
Unthreaded Mounting Hole Diameter:
Between 0.124 inches and 0.130 inches
Distance Between Mounting Facility Centers:
8.175 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Removable single mating end single contact grouping
Connector Locking Method:
Friction
Operating Tempurature Rating:
Between -65.0 degrees celsius and 125.0 degrees celsius
Features Provided:
Low insertion force contact
Terminal Location:
Side single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate glass filled single mating end and plastic polyester glass filled single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type ii, grade c, class 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290
federal specification 2nd treatment response single mating end single contact grouping
Torminal Type:

Insert Material Specification:

Printed circuit single mating end single contact grouping

Mil-m-24519, type gpt-15f military specification single material response single mating end

NSN 5935-01-444-3959

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity:
144 single mating end single contact grouping
Included Contact Type:
Brush pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.124 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-55302 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-c-55302/168 government specification
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.