

View Online at <https://aerobasegroup.com/nsn/5935-01-448-1235>

Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Straight shape, internal coupling

Overall Length:

2.020 inches

Overall Diameter:

1.062 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

Agac 10-6 single mating end

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

625.0 single mating end single contact grouping

Polarization Method:

Key or multiple key

Shell Type:

Solid

Connector Locking Method:

Internally threaded coupling ring

End Application:

Ext sig cbl

Thready Qty Per Inch (tpi):

14

Thread Size:

0.875 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping and steel single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Glass single mating end

Contact Surface Treatment Specification:

Mil-g-45204 type ii, class 1 military specification single treatment response single mating end single contact grouping

Shell Material:

Stainless steel

Shell Material Specification:

Qq-s-763 federal specification single material response

Insert Material Specification:

Mil-m-14f military specification single material response single mating end

Included Contact Quantity:

6 single mating end single contact grouping

Special Features:

Series ii glass sealed plug with solid glass bulkhead

Precious Material And Location:

Contact surfaces gold

Precious Material:

Gold

Thread Series Designator:

Un

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.