NSN 5935-01-452-6276

Thread Pitch Diameters: -0.10/+0.10 millimeters

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-452-6276

Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
32.5 millimeters
Overall Diameter:
38.1 millimeters
Distance From Mounting Shoulder To Front Face:
22.6 millimeters
Mounting Facility Thickness:
2.2 millimeters
Mating End Quantity:
1
Contact Position Arrangement Style:
13-8 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
Insert Position In Deg: 100.0 or 260.0
_
100.0 or 260.0
100.0 or 260.0 Shell Type:
100.0 or 260.0 Shell Type: Solid
100.0 or 260.0 Shell Type: Solid Connector Locking Method:
100.0 or 260.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling nut
100.0 or 260.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling nut Thread Size:
100.0 or 260.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling nut Thread Size: 28.0 millimeters
100.0 or 260.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling nut Thread Size: 28.0 millimeters Terminal Location:
100.0 or 260.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling nut Thread Size: 28.0 millimeters Terminal Location: Back single mating end single contact grouping
100.0 or 260.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling nut Thread Size: 28.0 millimeters Terminal Location: Back single mating end single contact grouping Contact Material:
Shell Type: Solid Connector Locking Method: Internally threaded coupling nut Thread Size: 28.0 millimeters Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping
Shell Type: Solid Connector Locking Method: Internally threaded coupling nut Thread Size: 28.0 millimeters Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment:
Shell Type: Solid Connector Locking Method: Internally threaded coupling nut Thread Size: 28.0 millimeters Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping
Shell Type: Solid Connector Locking Method: Internally threaded coupling nut Thread Size: 28.0 millimeters Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material:
Shell Type: Solid Connector Locking Method: Internally threaded coupling nut Thread Size: 28.0 millimeters Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Plastic epoxy single mating end
Shell Type: Solid Connector Locking Method: Internally threaded coupling nut Thread Size: 28.0 millimeters Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Plastic epoxy single mating end Terminal Type:
Shell Type: Solid Connector Locking Method: Internally threaded coupling nut Thread Size: 28.0 millimeters Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Plastic epoxy single mating end Terminal Type: Crimp single mating end single contact grouping

NSN 5935-01-452-6276

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Nickel
Fhread Tolerance Class:
6g internal
ncluded Contact Quantity:
3 single mating end single contact grouping
ncluded Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material:
Gold
Test Data Document:
31349-mil-c-38999/24 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
so m
Shelf Life:
N/a
Jnit Of Measure:
-
Demilitarization:
No
Filg:
A039b0