Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-452-9209

## **Body Style:**

Straight shape, external coupling strain relief

### **Environmental Protection:**

Vibration proof and weatherproof

# Mating End Quantity:

1

## **Contact Position Arrangement Style:**

28-12 single mating end

### **Contact Removability:**

Nonremovable single mating end single contact grouping

## **Contact Maximum Current Rating In Amps:**

22.0 single mating end single contact grouping

### Shell Type:

Solid

## Connector Locking Method:

Bayonet shell

## **Operating Tempurature Rating:**

Between -55.0 degrees celsius and 125.0 degrees celsius

### **Contact Material:**

Copper alloy single mating end single contact grouping

## **Contact Surface Treatment:**

Silver single mating end single contact grouping

### **Terminal Type:**

Crimp single mating end single contact grouping

### Shell Material:

Aluminum alloy

### Shell Surface Treatment:

Chromate and cadmium

## **Included Contact Quantity:**

26 single mating end single contact grouping

### Included Contact Type:

Round socket single mating end single contact grouping

### **Special Features:**

Waterproof to 35 ft. Of water; shell finish olive drab colored water

## **Precious Material And Location:**

Contacts silver

## **Precious Material:**

Silver

# Shelf Life:

N/a

### Unit Of Measure:

--

Electrical Receptacle Connector - Page 2 of 2

AeroBase Group

Demilitarization:

No

Fiig:

A039b0