

View Online at <https://aerobasegroup.com/nsn/5935-01-452-9212>

Body Style:

Straight shape, external coupling strain relief

Environmental Protection:

Vibration proof and weatherproof

Mating End Quantity:

1

Contact Position Arrangement Style:

36-10 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

22.0 single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Bayonet shell

Operating Temperature Rating:

Between -55.0 degrees celsius and 125.0 degrees celsius

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Silver single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Chromate and cadmium

Included Contact Quantity:

48 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Special Features:

Waterproof to 35 ft. Of water; shell finish olive drab colored water

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0