

View Online at <https://aerobasegroup.com/nsn/5935-01-456-4247>

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape, external coupling

**Overall Length:**

32.5 millimeters

**Overall Diameter:**

Between 41.0 millimeters and 41.6 millimeters

**Distance From Mounting Shoulder To Front Face:**

22.6 millimeters

**Mounting Facility Thickness:**

Between 1.58 millimeters and 3.20 millimeters

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

15-97 single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

95.0 and 141.0 and 208.0 and 236.0

**Shell Type:**

Solid

**Connector Locking Method:**

Externally threaded shell

**Thread Size:**

28.0 millimeters

**Thread Pitch In Millimeters:**

1.00

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Terminal Type:**

Crimp single mating end single contact grouping

**Shell Material:**

Stainless steel

**Thread Tolerance Class:**

6g external

**Included Contact Quantity:**

12 single mating end single contact grouping

**Included Contact Type:**

Round socket single mating end single contact grouping

**Precious Material And Location:**

Contact surface gold

**Precious Material:**

Gold

**Thread Series Designator:**

Iso m

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-c-38999 spec.