

View Online at <https://aerobasegroup.com/nsn/5935-01-457-5111>

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

32.5 millimeters

Overall Diameter:

Between 41.0 millimeters and 41.6 millimeters

Distance From Mounting Shoulder To Front Face:

22.6 millimeters

Mounting Facility Thickness:

Between 1.58 millimeters and 3.20 millimeters

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

15-97 single mating end

Contact Removability:

Removable single mating end all contact groupings

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

95.0 and 141.0 and 208.0 and 236.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Thread Length:

8.5 millimeters

Thread Size:

28.0 millimeters

Thread Pitch In Millimeters:

1.00

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Terminal Type:

Crimp single mating end all contact groupings

Shell Material:

Stainless steel

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416 federal specification single treatment response

Thread Tolerance Class:

6g external

Included Contact Quantity:

8 single mating end 2nd contact grouping

Included Contact Type:

Round pin single mating end all contact groupings

Test Data Document:

81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Iso m

Specification Data:

81349-mil-c-38999/24 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0