NSN 5935-01-458-1895

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-458-1895 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** 2.088 inches **Overall Height:** 0.654 inches **Overall Width:** 0.494 inches **Distance Between Mounting Facility Centers:** 1.852 inches **Threaded Device Type:** Mounting hole **Mating End Quantity: Contact Position Arrangement Style:** 44 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Polarization Method:** Mating end Between -55.0 degrees celsius and 125.0 degrees celsius

Shell Type: Solid **Connector Locking Method:** Friction **End Application:** C17a aircraft **Operating Tempurature Rating:** Thready Qty Per Inch (tpi): 40 **Thread Size:** 0.375 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping

NSN 5935-01-458-1895

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment: Gold single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate glass filled single mating end **Terminal Type:** Pin single mating end single contact grouping **Insert Material Specification:** Mil-m-14, ty sdg-f military specification single material response single mating end **Included Contact Quantity:** 44 single mating end single contact grouping **Included Contact Type:** Round socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.044 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.