Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-458-6129

Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
32.5 millimeters
Overall Diameter:
Between 29.9 millimeters and 30.5 millimeters
Distance From Mounting Shoulder To Front Face:
22.6 millimeters
Mounting Facility Thickness:
Between 1.58 millimeters and 3.20 millimeters
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
Sep-98 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
105.0 and 140.0 and 215.0 and 265.0
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Thread Size:
17.0 millimeters
Thread Pitch In Millimeters:
1.00
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Stainless steel
5101111535 SIEE1

## NSN 5935-01-458-6129

Electrical Receptacle Connector - Page 2 of 2



Thread Tolerance Class: 6g external Included Contact Quantity: 3 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

**Precious Material And Location:** 

Contact surface gold

**Precious Material:** 

Gold

**Thread Series Designator:** 

lso m

Shelf Life:

N/a

Unit Of Measure:

---

**Demilitarization:** 

No

Fiig:

A039b0