NSN 5935-01-458-6132

Thread Direction:

Right-hand **Body Style:**

Stainless steel

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-458-6132

Straight shape, external coupling **Overall Length:** 32.5 millimeters **Overall Diameter:** Between 29.9 millimeters and 30.5 millimeters **Distance From Mounting Shoulder To Front Face:** 22.6 millimeters **Mounting Facility Thickness:** Between 1.58 millimeters and 3.20 millimeters **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** Sep-98 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 105.0 and 140.0 and 215.0 and 265.0 Shell Type: Solid **Connector Locking Method:** Externally threaded shell Thread Size: 17.0 millimeters **Thread Pitch In Millimeters:** 1.00 **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:**

NSN 5935-01-458-6132

Electrical Receptacle Connector - Page 2 of 2



Thread Tolerance Class:	
6g external	
Included Contact Quantity:	
3 single mating end single contact grouping	
Included Contact Type:	
Round socket single mating end single contact grouping	
Precious Material And Location:	
Contact surface gold	
Precious Material:	
Gold	
Thread Series Designator:	
lso m	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A039b0	