## NSN 5935-01-458-8808

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-458-8808

Body Style:
Straight shape
Overall Length:
1.562 inches
Overall Height:
0.856 inches
Overall Width:
0.438 inches
Environmental Protection:
Humidity resistant and shock resistant and thermal shock resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
0.143 inches
Distance Between Mounting Facility Centers:
1.250 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
16 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Polarization Method:
Mating end
Connector Locking Method:
Friction
Terminal Location:
Back single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204 ty1, grade c military specification single treatment response single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Insert Material Specification:
Mil-m-14 ty sdg-f military specification single material response single mating end
Included Contact Quantity:
20 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

## NSN 5935-01-458-8808

Fiig: A039b0

Mil-std (military Standard):

Mil-g-45204 spec.

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.020 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-dtl-29748 specification specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in
specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on
certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-dtl-28748/4 government specification government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No