

View Online at <https://aerobasegroup.com/nsn/5935-01-459-4482>

Body Style:

Straight shape, flush mount

Overall Length:

0.954 inches

Overall Height:

3.110 inches

Overall Width:

2.000 inches

Environmental Protection:

Humidity resistant and salt water resistant and shock resistant and thermal shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

0.120 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

2.783 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.437 inches

Distance From Mounting Shoulder To Front Face:

0.891 inches

Mating End Quantity:

2

Contact Position Arrangement Style:

67m 2nd mating end

Contact Removability:

Removable all mating ends single contact grouping

Polarization Method:

Mating end

Shell Type:

Solid

Connector Locking Method:

Friction

Terminal Location:

Back all mating ends single contact grouping

Contact Material:

Copper alloy all mating ends single contact grouping

Contact Surface Treatment:

Gold all mating ends single contact grouping

Insert Material:

Plastic diallyl phthalate glass filled all mating ends or plastic epoxy all mating ends or plastic phenolic all mating ends

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response all mating ends single contact grouping

Terminal Type:

Crimp all mating ends single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Nickel

Shell Surface Treatment Specification:

Mil-c-26074 military specification single treatment response

Shell Material Specification:

Qq-a-591 federal specification single material response or qq-a-367 federal specification single material response or qq-a-250 federal specification single material response

Insert Material Specification:

Mil-m-14 ty gdi-30f or sdg-f military specification 1st material response all mating ends or allied chemical 1288 bx mfr ref 2nd material response all mating ends or mil-m-14 military specification 3rd material response all mating ends

Included Contact Quantity:

67 2nd mating end single contact grouping

Included Contact Type:

Round socket all mating ends single contact grouping

Special Features:

Rack and panel connector; modification part number suffix 0201

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.066 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.