## NSN 5935-01-460-0826

**Thread Class:** 

2a

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-460-0826

**Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 34.7 millimeters **Overall Diameter:** Between 58.4 millimeters and 60.0 millimeters **Distance From Mounting Shoulder To Front Face:** 22.6 millimeters **Mounting Facility Thickness:** Between 1.6 millimeters and 3.2 millimeters **Threaded Device Type:** Back shell and coupling facility and mounting bushing **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 25-20 single mating end **Contact Removability:** Removable single mating end all contact groupings **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 135.0 and 170.0 and 200.0 and 310.0 Shell Type: Solid **Connector Locking Method:** Externally threaded shell **Thread Size:** 37.0 millimeters and 1.625 inches and 44.0 millimeters **Thread Pitch In Millimeters:** 1.00 **Terminal Location:** Back single mating end all contact groupings **Contact Material:** Copper alloy single mating end all contact groupings **Contact Surface Treatment:** 

Insert Material:

Plastic epoxy single mating end

Gold single mating end all contact groupings

## NSN 5935-01-460-0826

Electrical Receptacle Connector - Page 2 of 2



## **Contact Surface Treatment Specification:** Mil-g-45204 military specification single treatment response single mating end all contact groupings **Terminal Type:** Crimp single mating end all contact groupings **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Cadmium **Shell Surface Treatment Specification:** Qq-p-416 federal specification single treatment response **Thread Tolerance Class:** 6g external **Included Contact Quantity:** 4 single mating end 2nd contact grouping **Bushing Accommodation Hole Shape:** Round w/flat **Included Contact Type:** Round socket single mating end 4th contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material:** Gold **Thread Series Designator:** Iso m and special acme Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Fiig: A039b0

Mil-std (military Standard):

Mil-g-45204 spec.