NSN 5935-01-460-1577

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-460-1577 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.421 inches **Overall Diameter:** 1.740 inches **Distance From Mounting Shoulder To Front Face:** 0.781 inches **Mounting Facility Thickness:** 0.125 inches **Threaded Device Type:** Back shell **Mating End Quantity: Contact Position Arrangement Style:** 18-8 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 and 92.0 and 152.0 and 222.0 and 342.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin Thready Qty Per Inch (tpi): **Thread Size:** 1.036 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping

Terminal Type:Crimp single mating end single contact grouping

NSN 5935-01-460-1577

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Stainless steel
Shell Surface Treatment:
Passivate
Included Contact Quantity:
8 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round w/flat
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material:
Gold
Thread Series Designator:
Uns
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-c-26500 spec.